

maart

	9	10	11	12	13	14
m	3	10	17	24	31	
d	4	11	18	25		
w	5	12	19	26		
d	6	13	20	27		
v	7	14	21	28		
z	1	8	15	22	29	
z	2	9	16	23	30	

3 Maart 1980

CB vrije communicatie met: BETA CB 307



Specificatie:

General		Transmitter	
Channels:	22 ch	RF power output:	0.5W
Controls:	Channel selector, Mode push switch (FM, PA), Volume with power switch, Squelch, Clarifier, RF gain, Noise Blanker ON/OFF switch	Modulation capability:	2KHz
Jacks:	Antenna, Microphone, PA and external speaker, Sele-call	Spurious & harmonic suppression:	Better than -81dB
LED meter:	Greens for signal strength, Reds for RF power output and PA output(VU)	Battery drain:	500mA at full power output
Lights:	Meter, Digital channel display, PA indicator, Transmit indicator, Noise Blanker indicator, Squelch indicator	Frequency stability:	0.005%
Frequency range:	26.965 MHz to 27.225 MHz	Receiver	
Dimensions:	203mm(W) x 62mm(H) x 195mm(D)	Sensitivity:	Better than 0.5uV for 10dB (S + N) /N
Weight:	1.85Kgs	Spurious rejection:	Less than 2nW
Supply voltage:	13.2V DC	Spurious radiation:	Less than 4 nW
Semiconductors:	25 transistors, 4 FET's 4 IC's, 33 diodes, 14 LED's	Squelch range:	1 to 1000uV
		Clarifier:	± 1.0KHz
		Audio output:	4W (EXT. SP. at 4 ohm)

PTT goedgekeurd onder nr. AC-05-270-7924-A

Importeur

alpha electronics

Singel 167 3112 GN Schiedam
Telefoon 010-269767, telex 23392 alpha.